

REMGRIT CARBIDE GRIT EDGE

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

RemGrit[®] carbide grit edge saw products including band saw blades, hacksaws, rod saws, hole saws, circle saws, jig saws and recip blades (SP263, 264, 265)

Date of preparation: December 1998

Prepared by: DISSTON COMPANY
Deerfield Industrial Park
South Deerfield, MA 01373
(413)-665-7676

2. COMPOSITION, INFORMATION ON INGREDIENTS Percent by Weight

Alloy Elements	CAS NO.	RemGrit AISI 6150 Backing	RemGrit Wc Rod Saw, Hacksaw, Jig & Recip	RemGrit Wc Hole Saw, Circle Saw & Band Saw
Carbon	7440-44-0	.48-.53		
Chromium	7440-47-3	.80-1.10		
Cobalt	7440-48-4		6-10	5.8
Iron	7439-89-6	Balance		
Manganese	7439-96-5	.70-.90		
Niobium	7440-03-1		.5 Max	
Phosphorus	7723-14-0	.025 Max		
Silicon	7440-21-3	.20-.35		
Sulfur	7704-34-9	.025 Max		
Tantalum	7440-25-7		1.5 Max	
Tantalum Carbide	12070-06-3			2.5
Titanium	7440-32-6		.5 Max	
Tungsten Carbide	11107-01-0		Balance	91.7
Vanadium	7440-62-2	.15 Min		

See Section 8 for exposure guidelines

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

The cutting tools (in the form of a cutting blade) listed in section 1, in their usual, unaltered, physical state pose little or no immediate health hazard. When subjected to cutting, burning, grinding, sawing, brazing, welding, etc. there may be some generation of hazardous fumes, and or dusts. Proper industrial hygiene practices such as the use of engineering control (i.e. local exhaust ventilation) and or administrative controls (applicable respiratory and other types of protective equipment) should be utilized to control exposure.

POTENTIAL HEALTH EFFECTS

Primary route of exposure: Inhalation of dusts from grinding or cutting.

3. HAZARDS IDENTIFICATION continued

Routes of entry: Inhalation: Yes Skin: No Ingestion: No Eyes: Yes

It should be noted that the cutting tools (in the form of a cutting blade) listed in section 1, in their usual, unaltered, physical state pose little or no immediate health hazard. When subjected to cutting, burning, grinding, sawing, brazing, welding, etc. there may be some generation of hazardous fumes, and or dusts. An evaluation as needed by an industrial hygiene professional to assess the feasibility of the use of engineering controls (i.e. local exhaust ventilation) and or administrative controls (applicable respiratory and other types of protective equipment) should be undertaken.

Acute Effects:

Excessive inhalation of metallic fumes and dusts may cause irritation to the respiratory system. In some instances, excessive inhalation may result in a condition known as “metal fume fever”. Some symptoms of metal fume fever include metallic taste in the mouth, dry throat, coughing, dyspnea, rales and flu-like fever. Onset of symptoms may begin as soon as a few hours after exposure and last from 12 to 48 hours.

Excessive exposure to metallic fumes and dust may also result in physical irritation of the skin and other mucous membranes.

Chronic Effects:

The following is an outline of the chronic effects of the individual components (representing $\geq 1\%$ or $\geq 1\%$ for carcinogens or potential carcinogens) listed in section 1 of this material safety data sheet:

Chromium: The metal form of chromium (found in these products) is of very little toxicity. Health hazard issues arise from hexavalent chromium generated from welding fume. Health effects include respiratory irritation, edema, ulcers of the mucous membranes and nasal itch. The NTP lists hexavalent chromium as known to be a human carcinogen. Chromium metal is listed as not classifiable as to carcinogenicity to humans.

Cobalt: Chronic exposure to cobalt fume or dust causes skin and respiratory system irritation. Exposure may also result in coughing, wheezing, asthma, and respiratory hypersensitivity. Although NTP or OSHA does not list cobalt as a carcinogen, some data suggests that cobalt is a carcinogen in laboratory animals with unknown relevance to humans.

Iron: Chronic exposure to iron oxide fume (generated during welding) and dust may result in benign pneumoconiosis and can be identified with x-rays. The x-ray shadows are indistinguishable from siderosis. Excessive concentrations may also cause respiratory system irritation.

Tantalum: Chronic exposure to tantalum oxide and dusts may result in respiratory system irritation. Animal studies suggest chronic exposure may result in pulmonary irritation.

Tantalum Carbide: Chronic exposure may result in conjunctivitis.

Tungsten Carbide: May cause “hard metal lung” with symptoms as described in acute overexposure. Chronic exposure (material also contains cobalt, nickel and other metals) may result in respiratory system irritation, loss of appetite, blood changes nausea, and cough. The literature suggests that airborne nickel dusts are capable of causing lung cancer. Nickel is listed in the NTP as reasonably anticipated to be a human carcinogen.

4. FIRST AID MEASURES

Inhalation: If a person breathes large amounts of this substance, move the exposed person to fresh air at once. If breathing has stopped, perform mouth to mouth resuscitation (trained personnel only). Keep the affected person warm and at rest. Get medical attention as soon as possible.

Skin: Immediately flush with large amounts of water. Use soap if available.

Ingestion: Get medical attention immediately. Take MSDS sheet to medical facility.

Eye: If this substance contacts the eyes, immediately wash the eyes with large amounts of water, occasionally lifting the lower and upper lids. Get medical attention immediately. Contact lenses should not be worn when working with this substance.

5. FIRE FIGHTING MEASURES

Flash Point: N/A

Special fire fighting procedures: N/A

Flammable limits: N/A

LEL/UEL: N/A

Unusual fire and explosion hazards: N/A

Extinguishing media: N/A

Note: (N/A – Not Applicable)

6. ACCIDENTAL RELEASE MEASURES

No special instructions are necessary.

7. HANDLING AND STORAGE

Utilize good housekeeping practices and prevent accumulations of dusts to aid in the control of airborne concentrations.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

Eye Protection Requirements:

Safety glasses should be worn when grinding or cutting. Face shields and safety glasses should be worn during welding or burning. Contact lenses should not be worn.

Skin Protection Requirements:

Gloves and barrier creams may be used to prevent cuts, skin sensitization and dermatitis.

Respiratory/ Ventilation Requirements:

In the event of exposure to dusts, fumes or misting, a health hazard survey by an industrial hygienist or related health and safety professional should be undertaken. Provide a NIOSH approved respirator.

Use local (preferred) or general exhaust ventilation to control airborne concentrations of dust and fumes below the Threshold Limit Value (TLV). Seek advice from a safety professional and/or industrial hygienist.

Component	CAS NO.	OSHA PEL	ACGIH TLV
Carbon	7440-44-0	3.5 mg/m ³ (as carbon black)	3.5 mg/m ³ (as carbon black)
Chromium	7440-47-3	1 mg/m ³	0.5 mg/m ³
Cobalt	7440-48-4	0.1 mg/m ³	0.02 mg/m ³
Iron	7439-89-6	10 mg/m ³ (as iron oxide)	5 mg/m ³ (as iron oxide)
Manganese	7439-96-5	5 mg/m ³ (ceiling limit)	0.2 mg/m ³
Niobium	7440-03-1	not available	not available
Phosphorus	7723-14-0	0.1 mg/m ³ (yellow)	0.02 ppm (yellow)
Silicon	7440-21-3	15 mg/m ³ (total)	10 mg/m ³
Sulfur	7704-34-9	not available	not available
Tantalum	7440-25-7	5 mg/m ³ (metal)	5 mg/m ³ (metal)
Tantalum Carbide	12070-06-3	not available	not available
Titanium	7440-32-6	not available	not available
Tungsten Carbide	11107-01-0	1 mg Ni/m ³	not available
Vanadium	7440-62-2	0.5 mg V ₂ O ₅ /m ³ (ceiling limit) (respirable dust, as V ₂ O ₅) 0.1 mg V ₂ O ₅ /m ³ (ceiling limit) (fume, as V ₂ O ₅)	0.05 mg/m ³ (respirable dust or fume, as V ₂ O ₅)



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance, Odor & Physical state: Solid, odorless, metal **Boiling point:** 4788°F – 9797°F
pH: N/A **Melting Point:** 2664°F – 5425°F
Vapor Pressure (mm Hg): N/A **Solubility in Water:** Insoluble
Vapor Density (Air = 1): N/A **Specific Gravity (H₂O = 1.0):** 5.24-16.65

Note: (N/A – Not Applicable)

Above represents available property ranges for materials (representing ≥1%) listed in section 1 of this material safety data sheet.

10. STABILITY AND REACTIVITY

Stability: Chemically stable.

Conditions to avoid: Avoid exposure to dust and or fumes.

Incompatibility (Specific materials to avoid): Reacts with strong acids to generate hydrogen gas.

Hazardous Decomposition or byproducts: Metallic oxides.

Hazardous polymerization: Will not occur.

11. OTHER INFORMATION

Coatings may be applied to some of the blades for protective purposes. While this constitutes a minor component of the product, it should be considered when evaluating health hazards during any potential dust/ fume generating operations. Applicable coating/ pigment MSDS's are available upon request.

To the best of our knowledge, the information contained herein is accurate. However, Disston Company assumes no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



DISSTONTM

www.disstontools.com

Telephone: 1-800-272-4436
1-800-446-8890
Fax: 1-800-654-1972
1-888-729-3004

International Telephone: 1-413-665-1262
International Fax: 1-413-665-8064
Technical Support Telephone: 1-888-303-4344
email: customer.service@disstontools.com